

SWING DOOR MANHATTAN LINE

<u>DOOR</u>	Interior framed glass door	single or double, push or pull; wire in front or wire behind; also within partition walls
	“Traditional hinge” integrated in the door profile or “Hinge180” for a 180° opening solution and improved installation and adjustment performance	exclusive and patented HenryGlass hinges
	Accessories and minimal perimeter profile (12x40 mm) in anodised aluminium	6 standard finishes: White, Black, Moka, Titanium, Brass, Silver; RAL on request
	Accessories: magnetic casing also with lock or privacy	provision for LIFE or CLIP by HenryGlass handles or other commercially available handles
	Customisable door with inglesine “GRID”	various models also custom
<u>GLASS</u>	Safety glass: tempered 10 mm thick or tempered/stratified 5+5 mm thick	certifications for tempering and layering processes available
	Glass with various aesthetic and covering effects	transparent, satin-finished; extralight transparent or satin-finished; bronze/graphite transparent or satin-finished; opaque lacquer with gloss or satin effect also RAL; reflective transparent, satin-finished, neutral/bronze/graphite; 3 mirror versions
	Customisable glass with many decorative possibilities, standard or custom	sandblast engraving or digital pigmentation techniques; textures, images, materials
	Stratified glass also available with wire mesh	Champagne, Gold, Bronze
<u>FRAME</u>	Installation on HenryGlass frame	Plain (completely concealed in masonry or plasterboard); Light (in aluminium, telescopic, traditional cover strips, can be integrated with LED lighting); S-Light (in aluminium, telescopic, minimal cover strips, can be integrated with LED lighting); Cube (in aluminium, telescopic, without cover strips, can also be

		used in the wall system in combination with fixed glass)
	Can also be installed on NON-HenryGlass frames	

CERTIFICATIONS

System Certifications

UNI EN ISO 9001 - Quality Management Systems

Product Certifications

UNI EN 12150 - Thermally toughened soda lime silicate safety glass

DIMENSIONS customisable to mm:

max. width at door 1025 mm

max. height at door 2850 mm

ATT.NE! For larger dimensions please request a quote at